


AUTONOTIVE INDUSTRY



AMITSUBISHI MATERIALS CORPORATION





There is a long history regarding the development and design of Automobiles leading back to over a 100 years.


Since the origins,

there has been an extensive advance in concept, new features and performance.

The present day automotive industry has grown into a huge industry reaching for further developments and prospects.

Mitsubishi Materials offers a wide range of cutting edge technological products that meet the ever demanding requirements from the Automotive Industry.

Mitsubishi Materials also offers materials that are frequently used in the Automotive Industry therefore making it possible to also supply the cutting tools that are required to machine these particular materials.



AUTOMOTIVE

	CATEGORY ENGINE PARTS	
	CYLINDER HEAD TOOLING	05
	CYLINDER BLOCK TOOLING	07
	CRANK SHAFT TOOLING	09
	CAM SHAFT TOOLING	10
	CON ROD TOOLING	10
	CATEGORY TRANSMISSION PARTS	
	TRANSMISSION CASE TOOLING	12
	VALVE BODY TOOLING	12
	STATOR TOOLING	12
	OUTPUT SHAFT TOOLING	13
	CVT PULLEY TOOLING	13
	GEAR TOOLING	14
	TORQUE CONVERTER COVER TOOLING	15
	CATEGORY AXLE PARTS	
	KNUCKLE ARM TOOLING	17
	HUB TOOLING	17
	DRIVE SHAFT & CVJ TOOLING	17
	CATEGORY BRAKE PARTS	
	DISC BRAKE CALIPER TOOLING	18
	DISC TOOLING	18
	CATEGORY ELECTRICAL PARTS	
	COMMON RAIL & INJECTOR TOOLING	20
	ABS TOOLING	20
	MOTOR TOOLING	20
	CATEGORY DIE AND MOULD	
	CRANK SHAFT MOULD TOOLING	21
	CON ROD MOULD TOOLING	21
	SIDE PANEL MOULD TOOLING	21
	CATEGORY NEWS	
	GENERAL, SPECIAL, PRODUCT	22



CATEGORY ENGINE PARTS

CYLINDER HEAD TOOLING


CYLINDER BLOCK TOOLING

CRANK SHAFT TOOLING

CAM SHAFT TOOLING

CON ROD TOOLING







VP10RT

Specifically designed for use with sintered materials.

Economical approach with performance equal to that of CBN.



MNS drill

finishes.

Employs 4 through coolant holes. Therefore when drilling aluminium alloys this offers improved welding resistance leading to prolonged tool life and higher surface



Valve finishing tool

(Valve seat face and the stem guide hole)

Plunge type (for machining centres) (Valve seat face)

Provides high accuracy machining of the seat and stem hole resulting in extremely high quality cylinder heads.

high quality cylinder heads.

Solid carbide qun reamer (Stem guide hole)

Solid carbide shank offering improved roundness, straightness and prolonged tool life.

U flute design to ensure effective coolant flow to improve chip disposal leading to higher surface finishes.

Traverse type (for special machines) (Valve seat face)

Employs a unique sliding device that provides high accuracy machining of the seat and stem hole resulting in extremely



"Zero" run out cutter, QM7000

A face milling tool that has a user friendly cutting edge height adjustment device to ensure minimum cutting edge run out. Can be used with the QM7000 arbor. High dynamic balance making it suitable for high speed machining applications.

MAE/MAS drills

MAE/MAS drills have a double margin, offering finished holes that do not require a reaming process.

Suitable for high speed machining of aluminium and cast irons.

CATEGORY **ENGINE PARTS** CYLINDER BLOCK TOOLING 0 Line boring bar (Crank shaft hole) Employs unique micro-boring unit devices that ensure that high dimensional accuracies can be Face milling achieved. cutter for solid CBN inserts Solid CBN (MBS140) face milling cutter for machining of cast irons. Suitable for both rough and finish machining of cast irons. "Zero" run out cutter, QM7000 A face milling tool that has a user friendly cutting edge height adjustment device to ensure minimum cutting edge run out. Can be used with the QM7000 arbor. High dynamic balance making it suitable for high speed machining applications.

MWS-DB/ MSL drills (Extra long type)

Non step drilling of holes 10~30D possible. Therefore offering high efficiency machining.

Possible to convert from special gun drill machines to general purpose machining

machines to general purpose machining centres, leading to high machining flexibility and performance.

AUTOMOTIVE

FINISHING Carbide inserts



FINISHING CBN inserts



ROUGHING Carbide inserts







Cylinder bore boring cutters (Roughing & Finishing)

The roughing boring tool uses a combination of a tool grade, that offers high speed & feed machining, and a suitable chip breaker, for reduced cutting resistance, so as to achieve improved machining efficiencies.

The finishing tool uses CBN inserts that can provide high wear resistance properties that lead to an increase in overall machining dimensions. The finishing tool also employs a diameter adjustment function ensuring that high machining accuracies can be achieved.

Light weight/ Quick change face milling cutters (Head locating face)

Quick change cutter.


A face milling cutter designed to be as light as possible so as to reduce the machine down time during tool changes.





Pelican double clamp tool holder

The combination of the high insert clamping rigidity and the overall strength of the pelican holder itself results in effective machining even under heavy interrupted or high feed machining with large tool overhangs.



Pin milling cutter (Rough machining of the crank pin)





CATEGORY **ENGINE PARTS**

CAM SHAFT TOOLING

CON ROD TOOLING




UE6110

(CVD coated grade for machining of steels)

A revolutionary tool grade offering both high crater and flank wear resistance that leads to higher machining stability and tool life management.

MWE/ MWS step drills The MWE/MWS drills can


be used to reduce the number of machining operations therefore reducing machining time and cost while maintaining high hole accuracies.




MWS-DB/MSL drills (Extra long type)

Non step drilling of holes 10~30D possible. Therefore offering high efficiency machining.

Possible to convert from special gun drill machines to general purpose machining centres, leading to high machining flexibility and performance.








AUTOMOTIVE

TRANSMISSION CASE TOOLING STATOR TOOLING

VALVE BODY TOOLING







machining applications.

OUTPUT SHAFT TOOLING

CVT PULLEY TOOLING



UE6110

(CVD coated grade for machining of steels)

A revolutionary tool grade offering both high crater and flank wear resistance that leads to higher machining stability and tool life management.



MBC020

(Coated CBN tool grade for machining of hardened materials)

MBC020 is a tool grade that can be used for continuous through to interrupted machining.

An extensive range of edge preparations are available to suit various machining applications.



MBC010

(Coated CBN tool grade for machining of hardened materials)

A high grade that enables high speed machining of hardened steels. Cutting speeds of over 300m/min are possible leading to an increase in overall machining efficiency.



GEAR TOOLING



A new range of diamond dressing tools encorporating the latest machining technology.



MWE/MWS drills (Small size)

Wavy cutting edge and a unique flute geometry provides effective chip disposal leading to lower cutting resistance and prolonged tool life.

Shaving cutter

High speed, high performance and longer tool life can be achieved using the surface treated STH shaving cutter and the irregular land type shaving cutter.

Broach

Mono-bloc helical broach offering high machining accuracies and lower running costs.

Hob

Carbide Miracle hobs.
(Al,Ti)N coated and Super Violet hobs for increased machining performance capable of high speed dry machining.

TORQUE CONVERTER COVER TOOLING



AZ chip breaker


The AZ chip breaker employs a unique chip breaker, high rake that results in smooth chip control, improved welding resistance, and prevents the development of burrs.


Multiple PCD reamer

The use of a multiple reamer enables a reduction in machining operations resulting in improvements in productivity and tool management.

MNS drill

Employs 4 through coolant holes.
Therefore when drilling aluminium alloys this offers improved welding resistance leading to prolonged tool life





15 / 16





CATEGORY BRAKE PARTS

DISC BRAKE CALIPER TOOLING DISC TOOLING

Side cutter and Customised cutter





UC5100 series

(CVD coated grade for machining of cast irons)

CVD, coated grade that uses a special process to ensure the surface of the insert is very smooth. This leads to excellent welding resistance, prolonged tool life and improved surface finishes.




MB5140 Solid CBN insert


Insert is manufactured from 100% CBN, therefore there are no limitations regarding depth of cut. This leads to higher machining efficiency and performance.

High fracture resistance properties leading to high speed and efficiency machining.





COMMON RAIL & INJECTOR TOOLING





CATEGORY ELECTRICAL PARTS

COMMON RAIL & INJECTOR TOOLING ABS TOOLING **MOTOR** TOOLING

MNS drill

Employs 4 through coolant holes.



Multiple PCD reamer

The use of a multiple reamer enables a reduction in machining operations resulting in improvements in productivity



MGS drill (Solid carbide gun drill)

High run out accuracies making it possible to carry out stable deep hole drilling even on general machines.

MSE miniature drill

The MSE miniature drill uses a tough substrate in combination with miracle coating. A unique flute geometry ensures effective chip control leading to longer tool




An end mill that uses a DLC coating for the machining of non-ferrous materials. The coating offers increased adhesion to the substrate. and increased hardness. Prolonged tool life and a reduction in overall costs can be obtained.



Double marqin drill

Wavy cutting edge and a unique flute geometry provides effective chip disposal. The drill has 4 margins that ensure high hole accuracies and roundness. When the drill exits the hole problems can tend to occur but the double margin can provide stable machining and prolonged tool

CATEGORY DIE AND MOULD



SRF ball end mill


The SRF is a finishing ball end mill.

Uses a high precision radius insert that offers machining accuracies comparable to a solid end mill.

As the tool is indexable there is no need for regrinding.

MSTAR end mills

General purpose end mill. Available in a wide range of sizes and geometries.



5RM2 ball end mill

The SRM2 is capable of rough through to semi finish machining.
The combination of a highly rigid body with high accuracy low resistance inserts enables efficient machining.

ÍMPACT MIRACLE **end mills**

An end mill series that uses
Impact Miracle coating.
Impact miracle coating offers
high hardness and
oxidation resistance.
Unique cutting edge
geometry leads to
increased chipping
resistance.
Suitable for
materials up
to 60HRC.

AJX cutter

The AJX high feed radius cutter is capable of feed rates that are up to 5 times higher than conventional tools therefore enabling high efficiency machining and an overall reduction in machining time.



5PX end mill

An end mill suitable for rough machining of deep faces.
Uses inserts that have a wavy geometry to reduce the overall cutting resistance and to improve the chip breaking performance.

MIRACLE NOVA end mills


A 2 flute ball nose end mill with a radius tolerance of ±2μm. The highly accurate geometry in combination with the high lubricity coating results in prolonged tool life and improved surface finishes.

CATEGORY NEWS

GENERAL, SPECIAL, PRODUCT









C500G



P200G



P210G



P010G



TOOLS NEWS MHE



TOOLS NEWS
MICRO-MGS



TOOLS NEWS MBC010




TOOLS NEWS MBC020



TOOLS NEWS **UE6110**



TOOLS NEWS **UC5105/UC5115**



Overseas Sales Offices

JAPAN

MITSUBISHI MATERIALS CORPORATION

Area Marketing & Operations Department KFC bldg., 8F, 1-6-1, Yokoami, Sumida-ku, Tokyo 130-0015 Japan TEL +81-3-5819-8772 FAX +81-3-5819-8773

USA

MITSUBISHI MATERIALS U.S.A. CORPORATION

17401 Eastman Street, Irvine, California, 92614, USA TEL +1-949-862-5100 FAX +1-949-862-5180

MEXICO

MMC METAL DE MEXICO, S.A. DE C.V.

Av. La Canada No.16, Parque Industrial Bernardo Quintana, El Marques, Queretaro, CP76246 Mexico TEL +52-442-221-6136 FAX +52-442-221-6134

BRAZIL

MMC-METAL DO BRASIL LTDA.

Rua Cincinato Braga, 340, 13th-Flor, Bela Vista-CEP 01333-010, São Paulo-SP, Brazil TEL +55-11-3266-7687 FAX +55-11-3287-8587

SINGAPORE

MMC METAL SINGAPORE PTE LTD.

10, Arumugam Road, #04-00 Lion Industrial Building, 409957, Singapore

TEL +65-6743-9370 FAX +65-6749-1469

INDIA

MMC HARDMETAL INDIA PVT. LTD.

No.10, 1st Floor, 80 Feet Road, R.M.V 2nd Stage, Bangalore - 560094 India

GERMANY

MMC HARTMETALL GmbH

Comeniusstr. 2, 40670 Meerbusch Germany TEL +49-2159-9189-0 FAX +49-2159-918966

UNITED KINGDOM

MMC HARDMETAL U.K. LTD

Mitsubishi House, Galena Close, B774AS Tamworth, U.K. TEL +44-1827-312312 FAX +44-1827-312314

FRANCE

MMC METAL FRANCE s.a.r.l.

Rue Jaques Monod 6, 91400 Orsay, France TEL +33-1-69 35 53 53 FAX +33-1-69 35 53 50

SPAIN

MITSUBISHI MATERIALS ESPAÑA, S.A.

Calle Emperador 2, 46136 Museros/Valencia, Spain TEL +34-96-144-1711 FAX +34-96-144-3786

ITALY

MMC ITALIA S.r.I.

V. le Delle Industrie 20/5, 20020 Milano Italy TEL +39-02 93 77 03 1 FAX +39-02 93 58 90 93

RUSSIA

MMC HARDMETAL RUSSIA OOO LTD.

UL. Bolschaja Pochtovaja, 36 Bldg.1, 105082 Moscow, Russia TEL +7-495-72558-85 FAX +7-495-98139-73

POLAND

MMC HARDMETAL POLAND SP. z o.o.

Al. Armii Karjowey 61, 40-541 Wroclaw, Poland TEL +48-71335-16-20 FAX +48-71335-16-21